

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B62B 1/00, B25H 5/00	A1	(11) International Publication Number: WO 99/59858 (43) International Publication Date: 25 November 1999 (25.11.99)
--	-----------	---

<p>(21) International Application Number: PCT/US99/07039</p> <p>(22) International Filing Date: 13 May 1999 (13.05.99)</p> <p>(30) Priority Data: 09/079,403 15 May 1998 (15.05.98) US</p> <p>(71) Applicant: REHRIG INTERNATIONAL, INC. [US/US]; 901 North Lombardy Street, Richmond, VA 23220 (US).</p> <p>(72) Inventors: KERN, Alan, R.; 10 W. Runswick Drive, Richmond, VA 23233 (US). PORTER, Terrill, M.; 9304 Broad Meadows Road, Glen Allen, VA 23060 (US).</p> <p>(74) Agents: KENNEY, J., Ernest et al.; Bacon & Thomas, PLLC, 4th floor, 625 Slaters Lane, Alexandria, VA 22314 (US).</p>	<p>(81) Designated States: BR, CA, MX, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>
---	---

(54) Title: DOLLY WITH ONE-PIECE PLASTIC FRAME



(57) Abstract

A dolly (10) with a one-step injection molded one-piece plastic frame (20) is provided. The frame (20) includes a pair of substantially parallel longitudinal side members (16) and a pair of substantially parallel transverse side members (18) which form a generally rectangular frame having corners (22). A bottom (14) of the dolly (10) is at least partially formed in a honeycomb/cellular configuration (24). A plurality of casters (30) are mounted to the bottom (14) of the frame (20) via a plurality of castor fastening bolts (28) which are received in a corresponding plurality of castor fastening holes (26) disposed at the corners (22). The dolly (10) may also include a riser block (42) disposed on a top (12) of the frame (20) along a side member (18) and secured to the frame (20) by the castor fastening bolts (28). A rubber pad (44) may be disposed on the riser block (42) and secured between the riser block (42) and the top (12) of the frame (20). The dolly (10) may also include a channel (36) in the bottom (14) of one or more side members (16) for receiving a reinforcing member (38).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DOLLY WITH ONE-PIECE PLASTIC FRAME

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to a dolly with a one-piece plastic frame. More specifically, the invention relates to a dolly with a one-step injection molded one-
5 piece plastic frame.

Brief Description of the Related Art

It is well known to provide a plastic dolly with a rectangular frame formed by connecting a plurality of frame members. Such dollies typically include casters which are connected to the frame by caster bolts which are also used to
10 secure the frame members together.

It is also known to include reinforcement elements in the frame members which are then assembled with the frame members to form the frame. It is also known to provide riser pads with protective caps for such a dolly. These riser pads and protective caps are similarly assembled with the frame members to form
15 the frame of the dolly.

These known dollies, however, have the disadvantage that the entire dolly and frame must be disassembled to change its configuration. For instance, if a riser pad or protective cap is damaged and needs to be replaced, bolts must be removed for replacement of the damaged parts and removal of these bolts
20 disassembles at least part of the frame. Also, if a different combination of reinforcement elements and/or riser blocks is required for supporting and transporting a specific load, the frame itself must at least partially be disassembled. This disassembly and reassembly of the frame itself may lead to

an undesirable weakening of the structural strength and stability of the dolly.

SUMMARY OF THE INVENTION

The present invention aims towards a plastic dolly which avoids the above-mentioned disadvantages, which is easy to manufacture and provides the advantages of known plastic dollies.

5 To this end, a dolly with a one-step injection molded one-piece plastic frame is provided. The one-piece plastic frame comprises a pair of substantially parallel longitudinal side members and a pair of substantially parallel transverse side members which form a generally rectangular frame having corners.

The dolly of the present invention includes a bottom which may be at least
10 partially formed in a honeycomb/cellular configuration to provide structural strength and stability.

The frame of the present invention includes a plurality of caster fastening holes disposed at the corners thereof. The caster fastening holes are formed to receive a corresponding plurality of caster fastening bolts for connecting a
15 plurality of casters to the bottom of the frame.

The casters may be mounted on a corresponding plurality of caster plates provided with caster plate holes through which the caster fastening bolts connect the caster plates to the bottom of the frame.

A side member of the frame may include a channel in the bottom thereof
20 which receives a reinforcing member. The channel may extend into the corners of the frame such that the reinforcing member is retained in the channel by the casters or the caster plates.

The dolly of the present invention may also include a riser block or blocks which may be disposed on a top of the frame along a side member and secured
25 to the frame at the corners by the caster fastening bolts.

The dolly of the present invention may also include a rubber pad or pads

which may be disposed on the riser block or blocks. The rubber pad may include rubber tabs which may be secured between the riser block and the top of the frame.

Various additional features and advantages of the dolly of the present invention will become clear upon a review of the detailed description and
5 accompanying drawings that follow.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to more particularly point out the features of the present invention, the following preferred embodiments are presented, as examples only without any limiting character, with reference to the accompanying drawings, in
10 which:

Figure 1 is an upper perspective view of a dolly according to the invention;

Figure 2 is a bottom perspective view of a frame of a dolly according to the invention;

15 Figure 3 is a side sectional view taken along the section line III-III shown in Figure 1; and

Figure 4 is an expanded perspective view of a dolly according to the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 As shown in Figure 1, a plastic dolly 10 having a top 12 and a bottom 14 comprises a pair of substantially parallel longitudinal side members 16 and a pair of substantially parallel transverse side members 18 which form a generally rectangular frame 20 having corners 22. Dolly 10 is injection molded in a single step. Therefore, longitudinal side members 16 and transverse side members 18

are integrally formed to obtain frame 20. One-step injection molding of a one-piece frame requires only single mold and does not require assembly of individual frame pieces.

As represented in Figure 2, bottom 14 is at least partially formed in a honeycomb/cellular configuration 24 to provide additional structural strength and stability while reducing the material required and overall weight of the dolly. Honeycomb/cellular configuration 24 may or may not extend into corners 22, but at least extends along side members 16 and 18 between corners 22.

A plurality of caster fastening holes 26 are formed in each corner 22. Caster fastening holes 26 receive a corresponding plurality of caster fastening bolts 28 for securing a plurality of casters 30 to bottom 14 of frame 20 at corners 22. Casters 30 may be secured to bottom 14 on a corresponding plurality of caster plates 32 by caster fastening bolts 28 extending through a corresponding plurality of caster plate holes 34.

Preferably, exactly three caster fastening holes 26 and three caster fastening bolts 28 are used at each corner 22. As shown in the figures, an "L" arrangement of caster fastening holes 26 at each corner 22 is preferred. Using exactly three caster fastening holes 26 in each corner 22 provides sufficient connecting strength while minimizing the number of caster fastening holes 26 which must be formed in frame 20 and the number of caster fastening bolts 28 which must be used.

As mentioned above, honeycomb/cellular configuration 24 may or may not extend into corners 22. Preferably it does not so that corners 22 of frame 20 are solid and thus provide strength to caster fastening holes 26 and stability to caster fastening bolts 28 disposed therein. If honeycomb/cellular configuration 24 does extend into corners 22, reinforcing plastic would be necessary at caster fastening holes 26 to provide similar strength and stability.

In a preferred embodiment, longitudinal side members 16 each include a longitudinal channel 36 in bottom 14 thereof. Longitudinal channels 36 are each

formed to receive a reinforcing member 38 which thereby extends in the respective longitudinal channel 36 along the respective longitudinal side member 16. Preferably, reinforcing members 38 comprise one-inch diameter steel tubes. It is not excluded, however, to use other materials, dimensions or shapes for reinforcing members 38. It is also not excluded to form channels 36, for
5 receiving reinforcing members 38, along transverse side members 18 instead of, or in addition to, forming channels 26 along longitudinal side members 16.

Channels 36 and reinforcing members 38 preferably extend into corners 22. Thus, reinforcing members 38 may be retained in channels 36 by casters 30, or caster plates 32, at corners 22.

10 A preferred embodiment, as represented in Figure 1, includes a riser block 42 disposed on top 12 of dolly 10 along transverse side members 18. It is not excluded, of course, to locate riser blocks 42 along longitudinal side members 16 instead of, or in addition to, along transverse side members 18. It is also contemplated by the present invention that multiple riser blocks 42 may be used
15 in combination to achieve a desired height.

As also represented in Figure 1, a preferred embodiment includes rubber pads 44 which fit over individual riser blocks 42. Rubber pads 44 provide a padded gripping surface for transporting an object on dolly 10 which itself may be relatively hard and provide relatively little friction.

20 Rubber pads 44 include rubber tabs 46 which are used to secure rubber pads 44 over riser blocks 42. Rubber tabs 46 are held or clamped between riser blocks 42 and top 12 of dolly 10. Caster fastening bolts 28 securing riser blocks 42 and casters 30 to frame 20 provide the clamping force. If multiple riser blocks 42 are stacked or used in combination, the specific dimensions of rubber pads 44
25 must be adjusted for rubber tabs 46 to be clamped between riser blocks 42 and top 12 of dolly 10.

As represented in Figure 4, the assembly of dolly 10 is simple and only involves securing casters 30, and possibly caster plates 32, reinforcing members

38, optional riser blocks 42 and optional rubber pads 44, to frame 20 using three
caster fastening bolts 28 in each corner 22. Therefore, dolly 10 itself will not be
structurally weakened by disassembly and reassembly to obtain different
combinations of reinforcing members 38, riser blocks 42 and rubber pads 44.
Frame 20 always maintains its integrity and structurally is not subject to wear
5 from disassembly and reassembly.

The present invention of a one-piece dolly is in no way limited to the
preferred embodiments described above and represented in the drawings; on the
contrary, various modifications may be made to such a one-piece dolly while
remaining within the scope of the invention, which is defined in the claims below.

We claim:

1. A dolly with a one-piece plastic frame, said dolly comprising:
a one-step injection molded one-piece generally rectangular plastic frame having a top and a bottom, said frame defining a pair of longitudinal side members and a pair of transverse side members, said longitudinal and transverse
5 side members intersecting at frame corners;
a plurality of caster fastening holes formed in each of said corners for receiving a corresponding plurality of caster fastening bolts which secure a plurality of casters having corresponding holes to said bottom of said frame at said corner;
10 a plastic riser block disposed on top of said frame at one of said transverse side members, said caster fastening holes continuing through said riser block; and
a plurality of caster fastening bolts corresponding to and extending through said caster fastening holes such that said riser block is connected to said top of said frame by said caster fastening bolts;
15 wherein said bottom of said frame is at least partially formed in a honeycomb/cellular configuration only along said transverse and longitudinal side members between said corners where said casters are to be secured.
2. A dolly according to claim 1, further comprising:
a rubber pad with rubber tabs, wherein said riser block has two entirely
20 flat bottom edges on opposite sides thereof, said rubber pad fitting over said riser block and being secured by said rubber tabs being retained between the entirely flat bottom edges of said riser block and said top of said frame under a clamping force exerted on said riser block and said frame by said caster fastening bolts.

FIG. 1





FIG. 2







FIG 4



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/07039

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B62B 1/00; B25H 5/00

US CL :280/79.11, 32.6

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 280/79.11, 32.6

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2,207,894 A (LOFTUS et al.) 15 February 1989 (15.02.89), see ABSTRACT and figures 1-3.	1-2
A	FR 1,485,314 A (HALDIMANN) 01 July 1966 (01.07.66), see figure 1.	1-2
A	US 4,824,129 A (REHRIG) 25 APRIL 1989 (25.04.89), entire document.	1-2
A	US 4,720,115 A (REHRIG) 19 January 1988 (19.01.88), entire document.	1-2

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

17 JUNE 1999

Date of mailing of the international search report

04 AUG 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

J. J. SWANN

Telephone No. (703) 305-0212